





Product Brochure

NO.	Items Name	Model	Photos (for reference)	Specification	Remark
1	Food Dehydrator commercial/industrial 80layers (Largest drying capacity)	FD-23		<p>Power: 6000W(Integrated power consumption:4800W per hour)</p> <p>Drying Tray Size:40*38CM</p> <p>Product Size: 53.5L*93.5W*167.5H(CM)</p> <p>Largest drying capacity in China market</p> <p>Quantity of trays:80(Upper and Lower rack gap:35mm)</p> <p>Digital control with touch control panel</p> <p>Single layer outershell</p> <p>Left&Right&Up&Down area with independent control.</p>	<p>Door handle can be both plastic and Aluminum</p> <p>With additional 4pcs crumb trays</p> <p>Material: 0.6-0.8mm thick SUS201 Stainless steel housing/SUS304 Stainless steel trays, handle, locks etc.</p> <p>Voltage: 220-240V/50Hz</p> <p>Time:0-24 hours adjustable</p> <p>Temperature setting range:30-90℃</p> <p>Operating noise: 45-50decibels</p> <p>Warranty:1 years (heating element for 3 years)</p> <p>Wooden box packing</p>
2	Food Dehydrator 12layers	FD-12		<p>Power: 1000W(Integrated power consumption:600W per hour)</p> <p>Drying Tray Size:39*28.3CM</p> <p>Product Size: 46.2L*40.2W*44.7H(CM)</p> <p>Quantity of trays:12(Upper and Lower rack gap:30mm)</p> <p>Digital control touch screen panel</p> <p>Door handle can be both plastic and Aluminum</p>	<p>With additional crumb tray</p> <p>Material: 0.6-0.8mm thick SUS201 Stainless steel housing/SUS304 Stainless steel trays, handle, locks etc.</p> <p>Voltage: 220-240V/50Hz, 110V/60Hz</p> <p>Time:0-24 hours adjustable</p> <p>Temperature setting range:30-90℃</p> <p>Operating noise: 45-50decibels</p> <p>Warranty:1 years (heating element for 3 years)</p>

Product Brochure

NO.	Items Name	Model	Photos (for reference)	Specification	Remark
3	Food Dehydrator commercial/industrial 48layers	FD-48		<p>Power: 4500W(Integrated power consumption:3600W per hour) Drying Tray Size:40*38CM Product Size: 55L*141W*79.5H(CM) Quantity of trays:48(Upper and Lower rack gap:35mm) Digital control with touch control Double layer outershell, Heat protection, Better drying performance Left&Middle&Right area with independent control. Top flat side can put around over 120KG things, Save more space. Door handle can be both plastic and Aluminum</p>	<p>With additional 3pcs crumb trays Material: 0.6-0.8mm thick SUS201 Stainless steel housing/SUS304 Stainless steel trays, handle, locks etc. Voltage: 220-240V/50Hz Time:0-24 hours adjustable Temperature setting range:30-90℃ Operating noise: 45-50decibels Warranty:1 years (heating element for 3 years) Wooden box packing</p>
4	Food Dehydrator commercial/industrial 6layers	FD-6		<p>Power:400W(Integrated power consumption:300W per hour) Drying Tray Size:28.5*20CM Product Size: 36L*30W*35.5H(CM) Quantity of trays:6(Upper and Lower rack gap:43mm) Digital control touch screen panel Door handle can be both plastic and Aluminum</p>	<p>With additional crumb tray Material: 0.6-0.8mm thick SUS201 Stainless steel housing/SUS304 Stainless steel trays, handle, locks etc. Voltage: 220-240V/50hz, 110V/60Hz Time:0-24 hours adjustable Temperature setting range:30~90℃ Operating noise: 45-50decibels Warranty:1 years (heating element for 3 years)</p>